



CAL-3104A



4-ch All-in-One H.264 Network DVR (ATM DVR)

Specifications*:	CAL-3104A
Operating System	: Embedded Linux operation system
System Resource	: 4 channel real-time video and network-wide transmission
Operation Interface	: Graphical User Interface (GUI), mouse, front button, remote control operation
Video Standard	: PAL, NTSC
Image Compression	: H.264
Audio Compression	: ADPCM
Recording Mode	: Manual, timing, motion detection
Video Search	: Time search, channel search, the log search
Backup	: Network backup, USB backup
Video Input/Output	: 4 BNC IN / 7" LCD Monitor, 1 BNC OUT , 1 VGA OUT
Audio Input/Output	: 4 channel / 1 channel
Monitoring Quality	: PAL: 720x576 (D1) ; NTSC: 720x480 (D1)
Video Quality	: PAL: 4 ch D1 (720x576) 25 fps/channel NTSC: 4 ch D1 (720x480) 30 fps/channel
Motion Detection	: 22 x 18 detection areas/channel, multi-level sensitivity can be set
Video Display Split	: 1, 4 image
Total Frame	: 100 fps (PAL) ; 120 fps (NTSC)
Video Recording	: PAL: 25 fps/channel (adjustable) ; NTSC: 30 fps/channel (adjustable)
Video Save	: Hard drive, network
Local Playback	: 1-4 D1 channel
PTZ	: RS485
Digital Zoom	: Support
Language	: Multi languages
Hard Disk	: Support one SATA HDD, 2 TB max.
Network Interface	: RJ45 10MB/100MB self-adaptive ethernet
USB Interface	: 2 USB 2.0 high-speed interface
P2P	: Support
Remote View	: CALview cloud (www.CALview.co & www.CALview.biz)
Working Temperature	: -10°C to 55°C
Working Humidity	: 10 to 90 % RH
Dimensions	:
Weight	:
Power	: 12 V

Supported features :



Supported browsers :



Supported OSs :



*The specifications are subject to change without notice

**Dimensional tolerance : ± 5 mm